

POWERKING®

Breaking New Grounds Since 1998

MKB

HYDRAULIC BREAKER



Manufactured in
Japan

Pioneer of hydraulic breakers

KONAN



■ SPECIFICATIONS

Model	Item	Weight with bracket & chisel (kg)	Overall length with chisel (mm)	Chisel diameter (φ) (mm)	Standard blowing frequency (blow/min.) <small>Numbers in parentheses () are for blowing frequency when switched over to high speed operations.</small>	Required oil flow rate (l/min.)	Operating oil pressure (Mpa)	Applicable excavator (ton)	Special applications
M Series	MKB60M	55	919	38	800~1,200	9~13	12.0~15.0	0.7~1.5	Non-accumulator mechanism Built-in control valve system
	MKB100M	75	1,019	45		15~22		1.2~2.5	
	MKB150M	150	1,272	55		30~45		2.5~4	
	MKB300M	250	1,611	70	550~1,100	35~70	12.0~16.0	4~7	
N Series	MKB500N	420	1,813	80	470~1,000	40~85	13.0~15.0	6~11	Non-accumulator mechanism Built-in control valve system
	MKB900N	820	2,154	100	440~750	65~110	14.0~17.0	10~15	
V Series	MKB1400V	1,400	2,550	130	360~480	100~130	15.0~18.0	16~20	Non-accumulator mechanism Impact frequency switch-over feature
	MKB1500V2	1,700	2,683	135	360~480 (430~570)	115~150		19~25	
	MKB1700V2	1,750	2,683	137	360~480 (430~570)	130~170		22~25	
	MKB2100V	2,400	2,846	150	340~450 (480~650)	135~180		25~40	Impact frequency switch-over feature
	MKB2500V	2,700	2,930	160	320~450 (460~630)	160~225		30~45	
	MKB3000V	3,300	3,245	165	300~450 (400~600)	170~260		40~50	
	MKB4000V	4,200	3,249	180	300~400 (430~570)	220~300		50~75	
	MKB6000V	5,900	3,581	200	250~380 (350~550)	220~330		75~100	

Manufacturer-specified chisels for different purposes

Point chisel (P type)



- Concrete crushing
- Rock crushing
- Road construction

Flat chisel (F type)



- Trenching
- Cutting of spouts, etc.
- Slope crushing

Flat-end chisel (FE type)



- Secondary crushing of broken stones
- Removing slag, etc.

※ Hard-core and long chisels are also available. ※ Please use a manufacturer-specified chisel with your MKB hydraulic breaker.

※ Please note that the specifications are subject to change without notice.

Exclusive Distributor

24/7
CUSTOMER SERVICE
ANYTIME, ANYWHERE.



Corporate Headquarters:

POWERKING

476 Edsa, Caloocan City

Tel. No.: **+632 364-6092**

Fax. No.: **+632 365-7460**

Email: sales@powerking.com.ph

www.powerking.com.ph

Regional Offices:

POWERKING

Subic

Lot3, Baton Area, Subic District,
Argonaut Highway, Subic Bay
Freepoint Zone

Tel. No.: **(047) 250-2331**

POWERKING

Cebu City

Ridgedale Subdivision
Tac-an Road, Talamban,
Cebu City

Tel. No.: **(02) 364-6092** (Manila)

POWERKING

Cagayan De Oro

National Highway, Brgy. Ipit,
Municipality of Opol,
Misamis Oriental

Tel. No.: **(088) 305-0032**